FLOWSTAR® SKIMMER WITH FLUSH FACE 4" EXTENSION, FLOAT ASSEMBLY, BASKET, LID AND COLLAR



Built in conformance with NSF 50 and SPS 3 standards

FEATURES

Designed for commercial and residential use, 15 GPM min, 90 GPM max

Adjustable collar

New weir clip lock secures the clips in the weir door

Large self-contained basket with lock-in feature (will not float)

Underwater dampers on the faceplate for noise reduction on weir plate - especially on windy days

Super strong engineered polymer upper housing

Extra heavy duty PVC lower unit (no transitional glue required)

21/2" outside slip and 2" inside slip (outside skimmer)

2" threads for pressure testing (inside skimmer)

1" built-in overflow or fill line knock-out

Upper housing has pre-cut rebar cutouts with predrilled holes for tie wire

Skimmer Lid and Collar G154 UV tested

Optional custom name/logo engraved on the lid (requires minimum 500 piece lid order)

1 per case

Two additional lid options available (sold separately): square or snap-in round/square





Optional vacuum plate with snap-in lug can be glued in under lid for easy storage p/n SK43101



Optional BFB adapter converts skimmer fittings to 4" or 3" tee for improved hydraulics and code compliance p/n BFB101

Part # SKR14xxx

STANDARD COLORS

SKR14101 - White

SKR14103 - Light Gray


SKR14105 - Dark Grav

Snap-in Round/Square Lid and Collar (sold separately) p/n SK65xxx, 8 per case

Square Lid and Collar (sold separately) p/n SK64xxx, 6 per case

NOTICE: For NSF certified skimmers, please contact your AquaStar Sales Representative. Lid, float valve, 4" socket, and 6" socket options are not NSF certified.


SPS 3 & NSF 50 Compliant





10. Weir Clip, Qty 2

- 7. Lid 4" Extension
- 2" Port Plug
- 3. Float Assembly
- 4. Basket
- 5. Basket Rod



10-11/32